

**SONY**Image not  
Available**VPLPX41**  
**SuperBright LCD Data Projector**List Price Not Available  
Price Varies - Please contact us for  
system pricing.**Description**

The VPLPX41 SuperBright LCD Data Projector is a flexible and powerful unit which can be used in many applications. Outputting 3500 ANSI Lumens, it is bright enough to light up very large screens while the high contrast ratio ensures crisp and detailed images. It features native XGA resolution, the ability to be tilted up or down by 90 degrees, TCP/IP network control, a unique password authentication system, a laser pointer remote control and can be fitted with optional lenses for applications which require a shorter or longer throw distance.

**Highlights**

- 16.5 lb Portable/Installation Projector
- 3500 ANSI Lumens Brightness
- High Contrast
- Native XGA Resolution with UXGA Compatibility via Compression
- Capable of 90 Degree Tilt Angles
- USB & Mouse Control
- Password Authentication Security Protection
- Dual Lamp Power Selection
- 4x Digital Zoom and Picture Freeze
- Audio Speakers: 2 Watt x 2
- Auto Input Search
- Direct Power ON/OFF
- TCP/IP Control Friendly
- Laser Pointer Remote Control

**Features****Feature**

- 3500 ANSI Lumens Brightness:
- XGA Native Resolution:
- High Contrast:

**Benefit**

The VPL-PX40 has enough brightness to fill large screens so that very large audiences can see your message and videos.

The newly designed LCD panels in the VPL-PX40 are 1024 pixels by 768 pixels (XGA) so that high resolution graphics from computers will be displayed with vivid detail and clarity.

Contrast ratio measures the difference between the brightest and darkest that a projector can display, and it is often more important than brightness. The VPL-PX40 has very high contrast so that images will be dynamic and captivating.

- Password Authentication System: The VPL-PX40 has a user selectable feature which allows the projector's use to be password protected. Once set, no one can turn the projector on until the proper password has been entered. Make sure to register your projector with Sony for the best protection!
- 90 Degree Tilt Angle: The VPL-PX40 can be tilted up, or down, up to 90 degrees. This is ideal for rear screen applications where space is at a premium and for applications where HoloScreens will be used.
- Direct Power On/Off: Many projectors need a cool down period or the expensive projector lamp may be damaged. This cool down period must be initiated by manual intervention or via an expensive control system. However, the VPL-PX40 can be connected to a simple wall switch for the purposes of powering the unit on and off. This means that there is no need for expensive control systems to correctly cycle unit power.
- Laser Pointer Remote Control: The VPL-PX40 is equipped with a user friendly remote control that features a laser pointer and computer mouse control. Using it and the USB port, presenters can be free to move about the room while making their presentation.
- TCP/IP Control Capability: Web based TCP/IP SNMP compliant Control System for remote control functions available on user's desktop. Functions such as power on and off can be accomplished via a LAN connection. E-mailing reporting system for immediate notification via email, pager etc of a failure as well as periodic Maintenance reminders.
- Optional Lenses: The VPL-PX40 can be equipped with an optional short throw or long throw lens.

## Specifications

<b>Specification</b>	<b>Detail</b>
<input type="checkbox"/> LCD PANEL	0.99 pSi TFT LCD
<input type="checkbox"/> LAMP	265W UHP LAMP
<input type="checkbox"/> LAMP LIFE	2000H / 3000H
<input type="checkbox"/> BRIGHTNESS	3500 ANSI LUMENS
<input type="checkbox"/> CONTRAST	500:1
<input type="checkbox"/> FAN NOISE	36 / 37 dB
<input type="checkbox"/> FILTER CLEANING	1500 Hours per Cleaning
<input type="checkbox"/> POWER CONSUMPTION	MAX. 365W
<input type="checkbox"/> DIMENSIONS	420 X 115 X 316 MM
<input type="checkbox"/> WEIGHT	APPROX 7.5 Kg (16.5lbs)
<input type="checkbox"/> RGB INPUTS	4 INPUTS
<input type="checkbox"/> DIGITAL INTERFACE	DVI-D Digital Visual Interface (Digital to Digital)
<input type="checkbox"/> 5BNC INPUT CONNECTOR	YES
<input type="checkbox"/> MAX INPUT RESOLUTION	UXGA

<input type="checkbox"/> 3D DIGITAL COMB. FILTER	YES
<input type="checkbox"/> SMART APA	YES
<input type="checkbox"/> 90 DEGREE TILT FREE ANGLE	Yes
<input type="checkbox"/> DIRECT POWER ON/OFF	YES
<input type="checkbox"/> REMOTE CONTROL	ETHER / RS-232C / CONTROLS

**Accessories****Optional:**

Model Name	Description	U.S. List Price
LMPP260	Replacement Lamp for the VPL-PX40 and VPL-PX41 Network LCD Data Projector	\$500.00
VPLKEYBOARD	Interlink Iwk-A100 Wireless Keyboard	\$199.00
VPLLFM22	Short Throw Lens For VPL-PX40 SuperBright LCD Data Projector	\$2,400.00
VPLLZM102	Long Throw Lens For The VPL-PX40 SuperBright LCD Data Projector	\$2,400.00
VPLLZM32	Projector Lens	\$2,400.00

like.no.other™

Copyright 2005 Sony Electronics Inc. All Rights Reserved | [Privacy Policy](#) | [Legal/Trademark](#)