

SONY®



Based on all the Features and Specs of the well-loaded PCM-R500; the PCM-R700 is also equipped with 4-Head Construction for Confidence monitoring.

NEW

PCM-R700

DIGITAL AUDIO RECORDER

FEATURES

- ▶ **4-Head Construction for Confidence Monitoring**
- ▶ **High-Reliability 4 D.D. Mechanical Transport**
Sony's legendary 4 D.D. Mechanism with 4 direct drive motors has been incorporated for a stable tape run. The PCM-R700 is also equipped with Auto Head Cleaning for improved sound quality.
- ▶ **Easy Operation with Shuttle and Jog Dial**
The handy Shuttle/Jog Dial provides easy system operation. Use the Shuttle for easy fast forward and rewind, or the Jog Dial for convenient Automatic Music Sensor™/Program Number.
- ▶ **Super Bit Mapping® Recording Function**
The Super Bit Mapping Recording Function achieves a S/N ratio equivalent to that of a 20-bit system.
- ▶ **Set-Up Menu for Preference Selection**
Use the convenient set-up menu for setting ID6, level sync threshold, date and more.
- ▶ **8-Pin Din Parallel Remote Interface**
- ▶ **Optional RM-D750 Wired Remote Commander®**
- ▶ **Wide Range of Audio Interface Options**
- ▶ **Adjustable (0.5s~9.5s) Auto Fade on Front Panel**
- ▶ **CH1/CH2 Independent Recording Level Volume Controls**
The PCM-R700 includes independent Channel 1/Channel 2 recording level volume controls to eliminate cross talk.

SPECIFICATIONS

Input/Output:

Analog input (Balanced)	XLR-3, Female
Reference level (Unbalanced)	+4dBu ~ -12dBu
/output (Balanced)	RCA-pin -12dBu
Reference level (Unbalanced)	XLR-3, Male
/output (Balanced)	+4dBu ~ -12dBu
Reference level (Unbalanced)	RCA-pin -12dBu
Digital input (AES/EBU)	XLR-3, Female
/output	XLR-3, Male
Digital input (Coaxial)	RCA Pin
/output	RCA Pin

Remote Interface:

REMOTE (8pin) DIN Connector (Parallel)
Optional Remote Commander input Mini plug (Serial)

General:

Power requirement: AC120V, 60Hz (for the U.S. and Canada)
Power consumption: 34W
Dimensions (W x H x D): Approx 482 x 145 x 355mm
Weight: Approx 7.4 kg

Supplied Accessories:

Wireless Remote Commander RM-D757 x 1
AC power cord x 1
Operation manual x 1

**Design and specifications are subject to change without notice.*